

ARROW

EXHAUST

NOTA TECNICA / TECHNICAL NOTICE

HONDA SH 125

HONDA	SH 125	EURO5+	EC ECE		VEICOLI CON DOPPIA Sonda LAMBDA VEHICLES WITH TWO OXIGEN SENSOR
VEHICLE TYPE: JF90					
 URBAN STEEL END CAP EC ECE HOMOL. ALUMINIUM "DARK" 53552AN		 URBAN STEEL END CAP RACING ALUMINIUM "DARK" 53052AN		 dB-KILLER PER TERMINALI URBAN RACING dB-KILLER FOR URBAN RACING SILENCERS 11023DB ALERT REMOVER DEVICE 11001EM	
 ATTENZIONE / ATTENTION 					
L'INSTALLAZIONE DELLO SCARICO RACING PUÒ PROVOCARE IL MESSAGGIO DI ERRORE «AVARIA MOTORE» WHEN INSTALLING A RACING FULL SYSTEM A WARNING MESSAGE «ENGINE FAILURE» MAY APPEAR					

IT	ALLARME CENTRALINA	EN	ECU ALERT
	l'installazione dello scarico completo racing può provocare un messaggio di errore che identifica il mancato rispetto dei parametri di funzionamento del catalizzatore. Installando quindi uno scarico racing Arrow, si consiglia l'installazione del dispositivo Arrow A.R.D. (11001EM).		When installing a racing full system, a warning message may appear identifying a deviation on catalytic converter functioning parameters. Therefore, when installing an Arrow racing exhaust, it is suggested to install the Arrow A.R.D. device, (11001EM).

ARROW SPECIAL PARTS S.P.A.

Via Citernese 128/130

06016 San Giustino (PG) - ITALY

Tel. +39.075.861.811 - Fax +39.075.861.81.37

www.arrow.it - info@arrow.it

